

# 4th Quarter Emissions Testing Report 2017

OneSteel Recycling Hexham



NATA ACCREDITATION No. 2778 (14391)

Accredited for compliance with ISO/IEC 17025 – Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

This document may not be reproduced except in full.

## 4th Quarter Emissions Testing Report 2017

OneSteel Recycling Hexham

Client: OneSteel Recycling Pty Ltd

ABN: 28 002 707 262

Prepared by

**AECOM Australia Pty Ltd**

17 Warabrook Boulevard, Warabrook NSW 2304, PO Box 73, Hunter Region MC NSW 2310, Australia

T +61 2 4911 4900 F +61 2 4911 4999 [www.aecom.com](http://www.aecom.com)

ABN 20 093 846 925

08-Dec-2017

Job No.: 60493017

AECOM in Australia and New Zealand is certified to ISO9001, ISO14001 AS/NZS4801 and OHSAS18001.

© AECOM Australia Pty Ltd (AECOM). All rights reserved.

AECOM has prepared this document for the sole use of the Client and for a specific purpose, each as expressly stated in the document. No other party should rely on this document without the prior written consent of AECOM. AECOM undertakes no duty, nor accepts any responsibility, to any third party who may rely upon or use this document. This document has been prepared based on the Client's description of its requirements and AECOM's experience, having regard to assumptions that AECOM can reasonably be expected to make in accordance with sound professional principles. AECOM may also have relied upon information provided by the Client and other third parties to prepare this document, some of which may not have been verified. Subject to the above conditions, this document may be transmitted, reproduced or disseminated only in its entirety.

## Quality Information

Document 4th Quarter Emissions Testing Report 2017

Ref 60493017


Date 08-Dec-2017

Prepared by Dylan Turnbull

Reviewed by Chad Whitburn AECOM Approved Signatory



### Revision History

Rev	Revision Date	Details	Authorised	
			Name/Position	Signature
0	08-Dec-2017	Report for Issue	Chad Whitburn Associate Director - Compliance Services	

## Table of Contents

1.0	Introduction	1
2.0	Sampling Plane Requirements	2
3.0	Methodology	3
	3.1 NATA Accredited Methods	3
	3.2 Equipment Calibration	3
4.0	Sampling Location	4
	4.1 Sampling Location Summary	4
5.0	Results	5
Appendix A		
	Field Sheets (17 pages)	A
Appendix B		
	Laboratory Results (8 pages)	B

## List of Tables

Table 1	Criteria for Selection of Sampling Planes (AS 4323.1)	2
Table 2	AECOM NATA Endorsed Methods	3
Table 3	Sampling Location Summary	4
Table 4	Shredder Baghouse Emission Results Summary, 23 November 2017	5
Table 5	Fine Particulate (PM <sub>10</sub> ), Total Particulate and Hazardous Substance (Metals) Results, 23 November 2017	6
Table 6	Hazardous Substances (Metals) Elemental Analysis Results, 23 November 2017	7

## 1.0 Introduction

AECOM was appointed by OneSteel Recycling Pty Ltd to conduct a series of measurements to determine air emissions from the Shredder Baghouse Stack (EPL Point 1) at the Hexham facility. Measurements were required for NSW EPA licence compliance (EPL No. 5345).

Testing was undertaken on 23 November 2017 to investigate emission concentrations for the following parameters:

- Fine Particulates (PM<sub>10</sub>);
- Total Particulate (TP); and
- Hazardous Substances (Metals) including Lead and Mercury.

Laboratory analysis was undertaken by the following laboratories which hold NATA accreditation for the specified tests:

- Steel River Testing, laboratory NATA accreditation number 18079, performed the following analysis detailed in report number 14892-0-M & 14892-0-P:
  - Total Particulate (TP);
  - Fine Particulates (PM<sub>10</sub>); and
  - Moisture.
- SGS Australia Pty Ltd NATA accreditation number 2562, performed the following analysis detailed in report number ME304956 R0:
  - Hazardous Substances (Metals).

## 2.0 Sampling Plane Requirements

The criteria for sampling planes are specified in AS 4323.1-1995 (R2014).

**Table 1 Criteria for Selection of Sampling Planes (AS 4323.1)**

Type of flow disturbance	Minimum distance upstream from disturbance, diameters (D)	Minimum distance downstream from disturbance, diameters (D)
Bend, connection, junction, direction change	>2D	>6D
Louvre, butterfly damper (partially closed or closed)	>3D	>6D
Axial fan	>3D	>8D (see Note)
Centrifugal fan	>3D	>6D

*NOTE: The plane should be selected as far as practicable from a fan. Flow straighteners may be required to ensure the position chosen meets the check criteria listed in Items (a) to (f) below.*

- a. *The gas flow is basically in the same direction at all points along each sampling traverse;*
- b. *The gas velocity at all sampling points is greater than 3 m/s;*
- c. *The gas flow profile at the sampling plane shall be steady, evenly distributed and not have a cyclonic component which exceeds an angle of 15° to the duct axis, when measured near the periphery of a circular sampling plane;*
- d. *The temperature difference between adjacent points of the survey along each sampling traverse is less than 10% of the absolute temperature, and the temperature at any point differs by less than 10% from the mean;*
- e. *The ratio of the highest to lowest pitot pressure difference shall not exceed 9:1 and the ratio of highest to lowest gas velocities shall not exceed 3:1. For isokinetic testing with the use of impingers, the gas velocity ratio across the sampling plane should not exceed 1.6:1; and*
- f. *The gas temperature at the sampling plane should preferably be above the dewpoint.*

With the exception of point 'b', the sampling plane was in accordance with AS4323.1. The gas stream velocities at each sampling point were found to be 2.4 m/s. Please note that the bag house was not running at full capacity at the time of testing.

## 3.0 Methodology

### 3.1 NATA Accredited Methods

The following methods are accredited with the National Association of Testing Authorities (NATA) (accreditation number 2778 (14391)) and are approved for the sampling and analysis of gases. Specific details of the methods are available on request.

All sampling and analysis is conducted according to the methods in **Table 2**.

**Table 2 AECOM NATA Endorsed Methods**

NSW EPA Approved Methods	USEPA Methods	Method Title
AS4323.1 (NSW EPA TM-1)	USEPA (2000) Method 1	Selection of sampling positions
AS4323.2 (NSW EPA TM-15)	USEPA (2000) Method 5 under approved circumstances	Determination of total particulate matter – isokinetic manual sampling – gravimetric method
NSW EPA TM-2	USEPA (2000) Method 2	Determination of stack gas velocity and volumetric flow rate (type s pitot tube)
NSW EPA TM-22	USEPA (2000) Method 4	Determination of moisture content in stack gases
NSW EPA TM-23	USEPA (2000) Method 3	Gas analysis for the determination of dry molecular weight
NSW EPA OM-5	USEPA (1997) Method 201 or 201A (as appropriate)	Determination of PM <sub>10</sub> emissions
NSW EPA TM-12,13 and 14	USEPA Method 29	Determination of metal emissions from stationary sources

All parameters are reported adjusted to 0°C at 1 atmosphere and dry gas.

### 3.2 Equipment Calibration

AECOM has a calibration schedule to ensure the emission testing equipment is maintained in good order and with known calibration. Equipment used in this project was calibrated according to the procedures and frequency identified in the AECOM calibration schedule. Details of the schedule and the calibration calculations are available on request.

## 4.0 Sampling Location

### 4.1 Sampling Location Summary

**Table 3** provides a summary of the location sampled by AECOM on 23 November 2017.

**Table 3 Sampling Location Summary**

Discharge Description	Shredder Baghouse Stack (EPL Point 1)
Duct Shape	Circular
Construction Material	Metal
Duct Diameter (mm)	760
Minimum No. Sampling Points	12
Sampling Ports	2
Min. Points/Traverse	6
Disturbance	No
Distance from Upstream Disturbance	6.6D
Type of Disturbance	Bend
Distance from Downstream Disturbance	2.6D
Type of Disturbance	Stack Exit
Ideal Sampling Location	Yes <sup>2</sup>
Correction Factors Applied	No
Total No. Points Sampled	12
Points/Traverse	6
Sampling Performed to Standard <sup>1</sup>	Yes <sup>2</sup>

<sup>1</sup> AS 4323.1 Section 4.1

<sup>2</sup> The sampling location was ideal in terms of flow disturbances, but did not comply with AS 4323.1 point b) as the corrected velocity of the gas at all sampling points was found to be 2.4 m/s (minimum 3m/s).  
D = Diameters



## 5.0 Results

A summary of air emission test results is shown in **Table 4**. Detailed results along with gas stream properties during the testing period can be found in **Table 5**. Speciated Hazardous Substances (Metals) results are presented in **Table 6**. Emission concentrations are converted to standard conditions of 0°C, dry gas and 1 atm pressure for comparison with regulatory limits.

Field sheets and final calculations recorded during the project are attached as **Appendix A**. Laboratory reports can be referred to in **Appendix B**.

AECOM has a calculated limit of uncertainty in regards to results. The estimation of measurement uncertainty in source testing is conducted to provide an indication of the precision of the measurement result and a degree of confidence in the range of values the reported result may represent. The measurement of uncertainty has been calculated at  $\pm 13.6\%$ .

**Table 4 Shredder Baghouse Emission Results Summary, 23 November 2017**

Parameter	Emission Concentration (EPL Point 1)	Emission Concentration Limit
Total Particulate (TP) (mg/m <sup>3</sup> )	0.62	100
Fine Particulate (PM <sub>10</sub> ) (mg/m <sup>3</sup> )	0.26	NA
Lead (mg/m <sup>3</sup> )	0.00017	5.0
Mercury (mg/m <sup>3</sup> )	<0.00017	1.0
Total Hazardous Substances (Metals) (mg/m <sup>3</sup> )	0.0030	NA

Results from testing conducted on EPL Point 1 on 23 November 2017 are below the regulatory limits listed in EPL 5345.

**Table 5 Fine Particulate (PM<sub>10</sub>), Total Particulate and Hazardous Substance (Metals) Results, 23 November 2017**

<b>Sampling Conditions:</b>		
Stack internal diameter at test location	760 mm	
Stack gas temperature (average)	21.5 °C	294.7 K
Stack pressure (average)	1017 hPa	
Stack gas velocity (average, stack conditions)	2.4 m/s	
Stack gas flowrate (stack conditions)	1.1 m <sup>3</sup> /s	
Stack gas flowrate (0°C, dry gas, 1 atm pressure)	0.99 m <sup>3</sup> /s	
<b>Fine Particulate (PM<sub>10</sub>) Testing</b>		
Test Period	7:36 -	9:07
Fine Particulate (PM <sub>10</sub> ) Mass	0.3 mg	
Gas Volume Sampled	1.2 m <sup>3</sup>	
Fine Particulate (PM <sub>10</sub> ) Emission* <sup>1</sup>	0.26 mg/m <sup>3</sup>	
Fine Particulate (PM <sub>10</sub> ) Mass Emission Rate* <sup>2</sup>	0.26 mg/s	
Regulatory Limit	NA	
<b>Total Particulate Testing</b>		
Test Period	7:36 -	9:07
Total Particulate Mass	0.7 mg	
Gas Volume Sampled	1.1 m <sup>3</sup>	
Total Particulate Emission* <sup>1</sup>	0.62 mg/m <sup>3</sup>	
Total Particulate Mass Emission Rate* <sup>2</sup>	0.61 mg/s	
Regulatory Limit	100 mg/m <sup>3</sup>	
<b>Hazardous Substances (Metals) Testing</b>		
Test Period	7:36 -	9:07
Hazardous Substances (Metals) Mass	0.0030 mg	
Gas Volume Sampled	1.2 m <sup>3</sup>	
Hazardous Substances (Metals) Emission* <sup>1</sup>	0.0026 mg/m <sup>3</sup>	
Hazardous Substances (Metals) Mass Emission Rate* <sup>2</sup>	0.0026 mg/s	
Regulatory Limit	NA	
<b>Moisture Content (%)</b>	<b>2.5</b>	
<b>Gas Density (dry at 1 atmosphere)</b>	<b>1.29 kg/m<sup>3</sup></b>	
<b>Dry Molecular Weight</b>	<b>28.8 g/g-mole</b>	

Notes \*1 Emission concentration at Standard conditions of 0°C, 1 atm, dry gas

\*2 Mass emission rate determined from pre and post-test sampling flow measurements and the respective test moisture content. See Q<sub>std</sub> in field sheets and final calculations "Stack Analysis - Final Calculations" for each test.

Table 6 Hazardous Substances (Metals) Elemental Analysis Results, 23 November 2017

Sample	Total Particulate Metals (mg)	Total Particulate Metals (mg/m <sup>3</sup> )	Total Gaseous Metals (mg)	Total Gaseous Metals (mg/m <sup>3</sup> )	Total Oxidisable Mercury (mg)	Total Oxidisable Mercury (mg/m <sup>3</sup> )	Total (mg)	Total (mg/m <sup>3</sup> )	Mass Emission Rate (mg/s)
Antimony	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Arsenic	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Beryllium	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Cadmium	0.0015	0.0013	0.00029	0.00025			0.002	0.0017	0.0017
Chromium	<0.001	<0.00086	0.00019	0.00016			0.00019	0.00016	0.00016
Cobalt	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Copper	<0.0012	<0.001	0.00029	0.00025			0.00029	0.00025	0.00025
Lead	0.0002	0.00017	<0.0002	<0.00017			0.0002	0.00017	0.00017
Magnesium	<0.058	<0.05	<0.0002	<0.00017			<0.002	<0.0017	<0.0017
Manganese	<0.0018	<0.0015	<0.0094	<0.008			<0.0002	<0.00017	<0.00017
Mercury	<0.0002	<0.00017	<0.0002	<0.00017	<0.0001	<0.000086	<0.0002	<0.00017	<0.00017
Nickel	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Selenium	0.0005	0.00043	<0.0013	<0.0011			0.0005	0.00043	0.00042
Thallium	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Tin	<0.0004	<0.00034	0.000087	0.000074			0.000087	0.000074	0.000073
Vanadium	<0.0053	<0.0045	<0.0042	<0.0036			<0.0002	<0.00017	<0.00017
Zinc	<1.401	<1.2	<0.001	<0.00086			<0.0002	<0.00017	<0.00017
<b>Total Hazardous Metals*</b>	<b>0.0022</b>	<b>0.0019</b>	<b>0.00048</b>	<b>0.00041</b>	<b>&lt;0.0001</b>	<b>&lt;0.000086</b>	<b>0.0030</b>	<b>0.0026</b>	<b>0.0026</b>
<b>Total Metals</b>	<b>0.0022</b>	<b>0.0019</b>	<b>0.00086</b>	<b>0.00073</b>			<b>0.0033</b>	<b>0.0028</b>	<b>0.0028</b>

\* Total does not include Copper, Magnesium and Zinc as they are classed non-hazardous

This page has been left blank intentionally.

# Appendix A

Field Sheets (17 pages)

## Appendix A Field Sheets (17 pages)

**Emission Measurement Calculations Spreadsheet****OneSteel Hexham**

AECOM's Project Number: 60493017

Emission Source: Shredder Stack

Date Sampled: 23-Nov-17

<b>ANALYTE(S)</b>	<b>METHOD</b>
Fine Particulate (PM10)	NSW EPA OM - 5
Total Particulate	NSW EPA TM - 15
Hazardous Substances (Metals)	NSW EPA TM - 12, 13 & 14



Observations made during testing period:

Sampling Performed By:

  
James Lang  
Dylan Turnbull

**STACK ANALYSIS - PRE-SAMPLING**

Date: 23-Nov-17  
 Client: OneSteel Hexham  
 AECOM's Project No: 60493017  
 Stack/Duct Description: Shredder Stack  
 Test 1: Fine Particulate (PM10)  
 Test 2: Total Particulate  
 Test 3: Hazardous Substances (Metals)

Measurement/Observations				
Stack Internal Dimensions:				
Diameter	760 mm	Cross Sectional Area :		0.45 m <sup>2</sup>
OR	Length Width			
Length/Width (mm)		Minimum No. of		
Equivalent Diameter	N/A mm	sampling points=		12
Distance from sampling plane to nearest disturbances:		Total No. of sampling points = 12		
Upstream (m) =	5	PM2.5/10=		12
No. Diameters =	6.6	No. of sampling traverses/ports sampled =		2
Type of Upstream Disturbance:	Fan Entry	PM2.5/10=		2
Downstream (m) =	2	No. of sampling points on each traverse/port =		6
No. Diameters =	2.6	PM2.5/10=		6
Type of Down Stream Disturbance:	StackExit	Exclusion of any sample point numbers - comments:		
Position of each sampling point, for each traverse:				
	A	B	PM10/2.5 A	PM2.5/10 B
No.	Distance from wall	S-type Pitot distances	Distance from wall	S-Type Pitot distances
1	33	3	33	3
2	111	81	111	81
3	225	195	225	195
4	535	505	535	505
5	649	619	649	619
6	727	697	727	697
7				
8				
9				
10			Check of total points against minimum, (yes/no) - comments:	
11				
12				
13				
14				
15				
16				
17				
18				
19			General Comments:	
20				
Signed: 		Checked: 		



ANZ

**Emission Measurement Calculations Spreadsheet**

Q4AN(EV)-332-FM31

**STACK ANALYSIS - GAS COMPOSITION AND DENSITY PRE-SAMPLING**

Date: 23-Nov-17  
 Client: OneSteel Hexham  
 AECOM's Project No: 60493017  
 Stack/Duct Description: Shredder Stack  
 Test 1: Fine Particulate (PM10)  
 Test 2: Total Particulate  
 Test 3: Hazardous Substances (Metals)

Sampling time start: 7:30		Sampling port No.: 1		
Measurement No.	Time sampled	CO (ppm). (dry)	O <sub>2</sub> (%), (dry)	CO <sub>2</sub> (%), (dry)
1	7:30	0	20.9	0.0
2	7:31	0	20.9	0.0
3	7:32	0	20.9	0.0
4	7:33	0	20.9	0.0
5	7:34	0	20.9	0.0
6	7:35	0	20.9	0.0
7	7:36	0	20.9	0.0
8	7:37	0	20.9	0.0
Averages:		0.0 ppm	20.9 %	0.0 %

Moisture content (M3): 0.99  
 Moisture percentage (M2): 0.60 %

Measurements

CO: 0.0000 %,(dry)	N <sub>2</sub> : 79.1 %,(dry)
CO <sub>2</sub> : 0.0 %,(dry)	O <sub>2</sub> : 20.9 %,(dry)
Gas Compositions converted to wet basis:	
CO: 0.0000 %,(wet)	N <sub>2</sub> : 78.6 %,(wet)
CO <sub>2</sub> : 0.0 %,(wet)	O <sub>2</sub> : 20.8 %,(wet)
H <sub>2</sub> O: 0.60 % (=M2)	
Therefore, stack gas density (GD) =	1.28 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure)
Therefore, stack gas density (GD) =	1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)

ANZ

**Emission Measurement Calculations Spreadsheet**

Q4AN(EV)-332-FM31

**STACK ANALYSIS - GAS COMPOSITION AND DENSITY POST-SAMPLING**

Date: 23-Nov-17  
 Client: OneSteel Hexham  
 AECOM's Project No: 60493017  
 Stack/Duct Description: Shredder Stack  
 Test 1: Fine Particulate (PM10)  
 Test 2: Total Particulate  
 Test 3: Hazardous Substances (Metals)

Sampling time start: 9:00		Sampling port No.: 1		
Measurement No.	Time sampled	CO (ppm). (dry)	O <sub>2</sub> (%), (dry)	CO <sub>2</sub> (%), (dry)
1	9:00	0	20.9	0.0
2	9:01	0	20.9	0.0
3	9:02	0	20.9	0.0
4	9:03	0	20.9	0.0
5	9:04	0	20.9	0.0
6	9:05	0	20.9	0.0
7	9:06	0	20.9	0.0
8	9:07	0	20.9	0.0
Averages:		0.0 ppm	20.9 %	0.0 %

Moisture content (M3): 0.98  
 Moisture percentage (M2): 2.39 %

Measurements

CO: 0.0000 %,(dry)	N <sub>2</sub> : 79.1 %,(dry)
CO <sub>2</sub> : 0.0 %,(dry)	O <sub>2</sub> : 20.9 %,(dry)
Gas Compositions converted to wet basis:	
CO: 0.0000 %,(wet)	N <sub>2</sub> : 77.2 %,(wet)
CO <sub>2</sub> : 0.0 %,(wet)	O <sub>2</sub> : 20.4 %,(wet)
H <sub>2</sub> O: 2.39 % (=M2)	
Therefore, stack gas density (GD) =	1.28 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure)
Therefore, stack gas density (GD) =	1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)











Emission Measurement Calculations Spreadsheet

Stack Analysis - Hazardous Substances Elemental Analysis Results

Date: 23-Nov-17 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

Metal	Particulate Metals Results	Gaseous Metals Results	Oxidisable Mercury Results		
	Front Half, Filter, Acetone Rinses and Acid Rinses (mg). Containers 1, 2 and 3	Back Half, Impingers + Acid Rinses (mg) Container 4	KO Impinger + Acid Rinses (mg) (5A)	KMnO <sub>4</sub> /H <sub>2</sub> SO <sub>4</sub> + Rinses (mg) (5B)	Residue Rinse 8N HCl (mg) (If Required) (5C)
Antimony	<0.0002	<0.0002			
Arsenic	<0.0002	<0.0002			
Beryllium	<0.0002	<0.0002			
Cadmium	0.0015	0.00029			
Chromium	<0.001	0.00019			
Cobalt	<0.0002	<0.0002			
Copper	<0.0012	0.00029			
Lead	0.0002	<0.0002			
Magnesium	<0.058	<0.0002			
Manganese	<0.0018	<0.0094			
Mercury	<0.0002	<0.0002	<0.0001	<0.0001	<0.0001
Nickel	<0.0002	<0.0002			
Selenium	0.0005	<0.0013			
Thallium	<0.0002	<0.0002			
Tin	<0.0004	0.000087			
Vanadium	<0.0053	<0.0042			
Zinc	<1.401	<0.001			

Note: Where the blank has returned a less than value, half of this value was subtracted from the sample result as a blank correction  
 ie for a blank value of <0.0005, 0.00025 was subtracted from the sample result.

\* Total does not include Copper, Magnesium and Zinc as they are classed non-hazardous

Stack Analysis - Hazardous Substances Elemental Analysis Results Continued

Date: 23-Nov-17 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

Sample	Total Particulate Metals (mg)	Total Particulate Metals (mg/m <sup>3</sup> )	Total Gaseous Metals (mg)	Total Gaseous Metals (mg/m <sup>3</sup> )	Total Oxidisable Mercury (mg)	Total Oxidisable Mercury (mg/m <sup>3</sup> )	Total (mg)	Total (mg/m <sup>3</sup> )	Mass Emission Rate (mg/s)
Antimony	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Arsenic	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Beryllium	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Cadmium	0.0015	0.0013	0.00029	0.00025			0.002	0.0017	0.0017
Chromium	<0.001	<0.00086	0.00019	0.00016			0.00019	0.00016	0.00016
Cobalt	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Copper	<0.0012	<0.001	0.00029	0.00025			0.00029	0.00025	0.00025
Lead	0.0002	0.00017	<0.0002	<0.00017			0.0002	0.00017	0.00017
Magnesium	<0.058	<0.05	<0.0002	<0.00017			<0.002	<0.0017	<0.0017
Manganese	<0.0018	<0.0015	<0.0094	<0.008			<0.0002	<0.00017	<0.00017
Mercury	<0.0002	<0.00017	<0.0002	<0.00017	<0.0001	<0.000086	<0.0002	<0.00017	<0.00017
Nickel	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Selenium	0.0005	0.00043	<0.0013	<0.0011			0.0005	0.00043	0.00042
Thallium	<0.0002	<0.00017	<0.0002	<0.00017			<0.0002	<0.00017	<0.00017
Tin	<0.0004	<0.00034	0.000087	0.000074			0.000087	0.000074	0.000073
Vanadium	<0.0053	<0.0045	<0.0042	<0.0036			<0.0002	<0.00017	<0.00017
Zinc	<1.401	<1.2	<0.001	<0.00086			<0.0002	<0.00017	<0.00017
Total Hazardous Metals*	0.0022	0.0019	0.00048	0.00041	<0.0001	<0.000086	0.0030	0.0026	0.0026
Total Metals	0.0022	0.0019	0.00086	0.00073			0.0033	0.0028	0.0028

\* Total does not include Copper, Magnesium and Zinc as they are classed non-hazardous



**STACK ANALYSIS - FINAL CALCULATIONS**

**Fine Particulate (PM10)**

(Calculations performed in accordance with relevant test method as defined on cover page)

Date: 23-Nov-17 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

(A) Sample gas volume at standard conditions

Metered volume (MV<sub>3</sub>): 1.2702 m<sup>3</sup> Average barometric pressure (P<sub>BARO</sub>) 1017 hPa  
 Average gas meter temp. (T<sub>M,2</sub>): 27.6 °C  
 300.8 K Average pressure at meter (P<sub>M,2</sub>) 1017.00 hPa  
 Sample gas volume (MV<sub>4</sub>); (0°C, dry gas, 1 atm pressure): 1.1579 m<sup>3</sup>

(B) PM10 concentration at standard conditions

Blank thimble No.: 0 Blank weight: g  
 Thimble No. used: T368 PM10 Weight: 0.0003 g  
 Final PM10 Weight (Mp1): 0.00030 g  
 PM10 Concentration (C1): =M<sub>p1</sub>/MV<sub>4</sub>= 0.00026 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure)  
 ;and C<sub>2</sub> = 0.26 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure)  
 CO<sub>2</sub> Basis 12 %  
 Average CO<sub>2</sub>%: 0.0 %

Therefore, C<sub>c</sub>: = C<sub>a</sub> x 12/CO<sub>2</sub>% = 0.00026 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)  
 ;and C<sub>c1</sub> = 0.26 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)

O<sub>2</sub> Basis 7 %  
 Average O<sub>2</sub>%: 20.9 %

Therefore, C<sub>b</sub>: =C<sub>a</sub> x (21 - O<sub>2ref</sub>%)/(21 - O<sub>2mea</sub>%) 0.036 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)  
 ;and C<sub>b1</sub> = 36 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)

(C) Moisture content

Silica Gel Number: F26  
 V<sub>v</sub> = 10.7 g (from laboratory report) V<sub>w</sub> = g mL (=grams) (recorded on Laboratory Form 108)  
 Volume of Water Vapour Condensed (V<sub>wc(std)</sub>) = 0.0120  
 Volume of Water Vapour Condensed (V<sub>wsg(std)</sub>) = 0.0143

Therefore, B<sub>ws</sub> =  $\frac{(V_{wc(std)} + V_{wsg(std)})}{(V_{wc(std)} + V_{wsg(std)} + V_{m(std)})}$

B<sub>ws</sub> = 2.22 %

ANZ

## Emission Measurement Calculations Spreadsheet

Q4AN(EV)-332-FM31

## STACK ANALYSIS - FINAL CALCULATIONS CONTINUED

## Fine Particulate (PM10)

## (D) Gas Composition and Density (Re-calculation)

(i) Initial gas density for sampling:	1.28 kg/m <sup>3</sup> (from Laboratory Form 107)
(ii) Re-calculated gas density based on moisture content in (c):	1.30 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure) 1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)
(iii) Gas density at stack conditions =	(ii) x $\frac{(273.2)}{(273.2+T_s)}$ x $\frac{(P_s)}{(1013.25)}$
=	1.210 kg/m <sup>3</sup> (stack conditions, wet)

## (E) Gas Velocities

(i) Average of pre-sampling velocities:	2.40 m/s
(ii) Average of post-sampling velocities:	2.40 m/s
(iii) Average of while-sampling velocities:	N/A m/s
(iv) Overall average of pre-sampling and post-sampling velocities (Vs):	2.40 m/s (stack conditions, wet) N/A m/s (stack conditions, wet)

(Note: (Vs) is from all individual data, **not** from (i) and (ii) alone.)

## (F) Volumetric Flowrates (Reference Method US-EPA Method 2, NSW-EPA TM-2)

$$Q_{stack} = V_s \times A = 1.09 \text{ m}^3/\text{s} \text{ (stack conditions)}$$

$$Q_{std} = Q_{stack} \times \frac{P_s}{(P_{std})} \times \frac{(T_{std})}{(T_s)} \times \frac{(100 - B_w)}{100}$$

$$Q_{std} = 1.0 \text{ m}^3/\text{s} \text{ (0°C, dry gas, 1 atm pressure)}$$

## (G) Mass Emission Rate

$$R_m = C_{1a} \times Q_{std} = 0.00026 \text{ g/s (0°C, dry gas, 1 atm pressure)}$$

$$= 0.26 \text{ mg/s (0°C, dry gas, 1 atm pressure)}$$

**STACK ANALYSIS - FINAL CALCULATIONS**

**Total Particulate**

(Calculations performed in accordance with relevant test method as defined on cover page)

Date: 23-Nov-17 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

(A) Sample gas volume at standard conditions

Metered volume (MV <sub>3</sub> ):	1.2225 m <sup>3</sup>	Average barometric pressure (P <sub>BARO</sub> ):	1017 hPa
Average gas meter temp. (T <sub>M,2</sub> ):	25.8 °C	Average pressure at meter (P <sub>M,2</sub> ):	1017.00 hPa
	299.0 K		
Sample gas volume (MV <sub>4</sub> ); (0°C, dry gas, 1 atm pressure):	1.1211 m <sup>3</sup>		

(B) Total Particulate concentration at standard conditions

Blank thimble No.:		Blank weight:	g
Thimble No. used:	T523	Total Particulate Weight:	0.0007 g
Final Total Particulate Weight (Mp1):	0.00070 g		
Total Particulate Concentration (C1):	= M <sub>p1</sub> /MV <sub>4</sub> =		0.00062 g/m <sup>3</sup> (0°C, dry gas, 1 atm pressure)
			0.62 mg/m <sup>3</sup> (0°C, dry gas, 1 atm pressure)

CO<sub>2</sub> Basis 12 % ;and C<sub>2</sub> = 0.62 mg/m<sup>3</sup> (0°C, dry gas, 1 atm pressure)  
 Average CO<sub>2</sub>%: 0.0 %

Therefore, C<sub>c</sub>: = C<sub>a</sub> x 12/CO<sub>2</sub>% = 0.00062 g/m<sup>3</sup> (0°C, dry gas, 1 atm pressure, 12% CO<sub>2</sub>)  
 ;and C<sub>c1</sub> = 0.62 mg/m<sup>3</sup> (0°C, dry gas, 1 atm pressure, 12% CO<sub>2</sub>)

O<sub>2</sub> Basis 7 %  
 Average O<sub>2</sub>%: 20.9 %

Therefore, C<sub>b</sub>: = C<sub>a</sub> x (21 - O<sub>2ref</sub>%)/(21 - O<sub>2mea</sub>%) = 0.087 g/m<sup>3</sup> (0°C, dry gas, 1 atm pressure, 7% O<sub>2</sub>)  
 ;and C<sub>b1</sub> = 87 mg/m<sup>3</sup> (0°C, dry gas, 1 atm pressure, 7% O<sub>2</sub>)

(C) Moisture content

Silica Gel Number:	135		
V <sub>v</sub> =	16.2 g (from laboratory report)	V <sub>w</sub> =	4 mL (=grams) (recorded on Laboratory Form 108)
Volume of Water Vapour Condensed (V <sub>wc(std)</sub> ) =	0.0053		
Volume of Water Vapour Condensed (V <sub>wsg(std)</sub> ) =	0.0216		

Therefore, B<sub>ws</sub> =  $\frac{(V_{wc(std)} + V_{wsg(std)})}{(V_{wc(std)} + V_{wsg(std)} + V_{m(std)})}$

B<sub>ws</sub> = 2.35 %

ANZ

## Emission Measurement Calculations Spreadsheet

Q4AN(EV)-332-FM31

## STACK ANALYSIS - FINAL CALCULATIONS CONTINUED

## Total Particulate

## (D) Gas Composition and Density (Re-calculation)

(i) Initial gas density for sampling:	1.28 kg/m <sup>3</sup> (from Laboratory Form 107)
(ii) Re-calculated gas density based on moisture content in (c):	1.30 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure) 1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)
(iii) Gas density at stack conditions =	(ii) x $\frac{(273.2)}{(273.2+T_s)} \times \frac{(P_s)}{(1013.25)}$
=	1.210 kg/m <sup>3</sup> (stack conditions, wet)

## (E) Gas Velocities

(i) Average of pre-sampling velocities:	2.40 m/s
(ii) Average of post-sampling velocities:	2.40 m/s
(iii) Average of while-sampling velocities:	N/A m/s
(iv) Overall average of pre-sampling and post-sampling velocities (Vs):	2.40 m/s (stack conditions, wet) N/A m/s (stack conditions, wet)

(Note: (Vs) is from all individual data, **not** from (i) and (ii) alone.)

## (F) Volumetric Flowrates (Reference Method US-EPA Method 2, NSW-EPA TM-2)

$$Q_{stack} = V_s \times A = 1.09 \text{ m}^3/\text{s} \text{ (stack conditions)}$$

$$Q_{std} = Q_{stack} \times \frac{P_s}{(P_{std})} \times \frac{(T_{std})}{(T_s)} \times \frac{(100 - B_w)}{100}$$

$$Q_{std} = 1.0 \text{ m}^3/\text{s} \text{ (0°C, dry gas, 1 atm pressure)}$$

## (G) Mass Emission Rate

$$R_m = C_{1a} \times Q_{std} = 0.00061 \text{ g/s (0°C, dry gas, 1 atm pressure)}$$

$$= 0.61 \text{ mg/s (0°C, dry gas, 1 atm pressure)}$$

**STACK ANALYSIS - FINAL CALCULATIONS**

**Hazardous Substances (Metals)**

(Calculations performed in accordance with relevant test method as defined on cover page)

Date: 23-Nov-17 Client: OneSteel Hexham  
 AECOM's Project No: 60493017 Stack/Duct Description: Shredder Stack

(A) Sample gas volume at standard conditions

Metered volume (MV <sub>3</sub> ):	1.2847 m <sup>3</sup>	Average barometric pressure (P <sub>BARO</sub> ):	1017 hPa
Average gas meter temp. (T <sub>M,2</sub> ):	28.2 °C	Average pressure at meter (P <sub>M,2</sub> ):	1017.00 hPa
	301.4 K		
Sample gas volume (MV <sub>4</sub> ); (0°C, dry gas, 1 atm pressure):	1.1688 m <sup>3</sup>		

(B) Metals concentration at standard conditions

Blank thimble No.:		Blank weight:	g
Thimble No. used:	0	Metals Weight:	0.000003 g
Final Metals Weight (Mp1):	0.00000 g		
Metals Concentration (C1):	=M <sub>p1</sub> /MV <sub>4</sub> =		2.6E-06 g/m <sup>3</sup> (0°C, dry gas, 1atm pressure)
			and C <sub>2</sub> =
CO <sub>2</sub> Basis	12 %		0.0026 mg/m <sup>3</sup> (0°C, dry gas, 1atm pressure)
Average CO <sub>2</sub> %:	0.0 %		

Therefore, C<sub>c</sub>: = C<sub>a</sub> x 12/CO<sub>2</sub>% = 0.0000026 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)  
 ;and C<sub>c1</sub> = 0.0026 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 12% CO<sub>2</sub>)

O<sub>2</sub> Basis 7 %  
 Average O<sub>2</sub>%: 20.9 %

Therefore, C<sub>b</sub>: =C<sub>a</sub> x (21 - O<sub>2ref</sub>%)/(21 - O<sub>2mea</sub>%) = 0.00036 g/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)  
 ;and C<sub>b1</sub> = 0.36 mg/m<sup>3</sup> (0°C, dry gas, 1atm pressure, 7% O<sub>2</sub>)

(C) Moisture content

Silica Gel Number: DT10  
 V<sub>v</sub> = 15.5 g (from laboratory report) V<sub>w</sub> = 8 mL (=grams) (recorded on Laboratory Form 108)  
 Volume of Water Vapour Condensed (V<sub>wc(std)</sub>) = 0.0107  
 Volume of Water Vapour Condensed (V<sub>wsg(std)</sub>) = 0.0207

Therefore, B<sub>ws</sub> =  $\frac{(V_{wc(std)} + V_{wsg(std)})}{(V_{wc(std)} + V_{wsg(std)} + V_{m(std)})}$

B<sub>ws</sub> = 2.61 %

## Emission Measurement Calculations Spreadsheet

## STACK ANALYSIS - FINAL CALCULATIONS CONTINUED

## Hazardous Substances (Metals)

## (D) Gas Composition and Density (Re-calculation)

(i) Initial gas density for sampling:	1.28 kg/m <sup>3</sup> (from Laboratory Form 107)
(ii) Re-calculated gas density based on moisture content in (c):	1.30 kg/m <sup>3</sup> (0°C, wet, 1 atm pressure) 1.29 kg/m <sup>3</sup> (0°C, dry, 1 atm pressure)
(iii) Gas density at stack conditions =	(ii) x $\frac{(273.2)}{(273.2+T_s)} \times \frac{(P_s)}{(1013.25)}$
=	1.210 kg/m <sup>3</sup> (stack conditions, wet)

## (E) Gas Velocities

(i) Average of pre-sampling velocities:	2.40 m/s
(ii) Average of post-sampling velocities:	2.40 m/s
(iii) Average of while-sampling velocities:	N/A m/s
(iv) Overall average of pre-sampling and post-sampling velocities (Vs):	2.40 m/s (stack conditions, wet) N/A m/s (stack conditions, wet)

(Note: (Vs) is from all individual data, not from (i) and (ii) alone.)

## (F) Volumetric Flowrates (Reference Method US-EPA Method 2, NSW-EPA TM-2)

$$Q_{stack} = V_s \times A = 1.09 \text{ m}^3/\text{s} \text{ (stack conditions)}$$

$$Q_{std} = Q_{stack} \times \frac{P_s}{(P_{std})} \times \frac{(T_{std})}{(T_s)} \times \frac{(100 - B_w)}{100}$$

$$Q_{std} = 1.0 \text{ m}^3/\text{s} \text{ (0°C, dry gas, 1 atm pressure)}$$

## (G) Mass Emission Rate

$$R_m = C_{1a} \times Q_{std} = 0.0000026 \text{ g/s (0°C, dry gas, 1 atm pressure)}$$

$$= 0.0026 \text{ mg/s (0°C, dry gas, 1 atm pressure)}$$

EMISSION MONITORING RESULTS, SHREDDER STACK ONESTEEL HEXHAM 23-Nov-17 FINE PARTICULATE (PM10) TOTAL PARTICULATE HAZARDOUS SUBSTANCES (METALS)		
<b>Sampling Conditions:</b>		
Stack internal diameter at test location	760 mm	
Stack gas temperature (average)	21.5 °C	294.7 K
Stack pressure (average)	1017 hPa	
Stack gas velocity (average, stack conditions)	2.4 m/s	
Stack gas flowrate (stack conditions)	1.1 m <sup>3</sup> /s	
Stack gas flowrate (0°C, dry gas, 1 atm pressure)	0.99 m <sup>3</sup> /s	
<b>Fine Particulate (PM10) Testing</b>		
Test Period	7:36	9:07
Fine Particulate (PM10) Mass	0.3 mg	
Gas Volume Sampled	1.2 m <sup>3</sup>	
Fine Particulate (PM10) Emission*1	0.26 mg/m <sup>3</sup>	
Fine Particulate (PM10) Mass Emission Rate*2	0.26 mg/s	
Regulatory Limit	NA	
<b>Total Particulate Testing</b>		
Test Period	7:36	9:07
Total Particulate Mass	0.7 mg	
Gas Volume Sampled	1.1 m <sup>3</sup>	
Total Particulate Emission*1	0.62 mg/m <sup>3</sup>	
Total Particulate Mass Emission Rate*2	0.61 mg/s	
Regulatory Limit	100 mg/m <sup>3</sup>	
<b>Hazardous Substances (Metals) Testing</b>		
Test Period	7:36	9:07
Hazardous Substances (Metals) Mass	0.0030 mg	
Gas Volume Sampled	1.2 m <sup>3</sup>	
Hazardous Substances (Metals) Emission*1	0.0026 mg/m <sup>3</sup>	
Hazardous Substances (Metals) Mass Emission Rate*2	0.0026 mg/s	
Regulatory Limit	NA	
<b>Moisture Content (%)</b>	2.5	
<b>Gas Density (dry at 1 atmosphere)</b>	1.29 kg/m <sup>3</sup>	
<b>Dry Molecular Weight</b>	28.8 g/g-mole	

Notes: \*1 Emission concentration at Standard conditions of 0°C, 1 atm, dry gas

\*2 Mass emission rate determined from pre and post test sampling flow measurements and the respective test moisture content. See Q<sub>std</sub> in field sheets and final calculations "Stack Analysis - Final Calculations" for each test.





# Appendix B

Laboratory Results  
(8 pages)

## Appendix B Laboratory Results (8 pages)

# Steel River Testing

5/11 McIntosh Drive, Mayfield West, NSW 2304

Phone: 02 49677880

## STACK EMISSION - PARTICULATES REPORT

**Origin:** AECOM - Newcastle

**Report :** 14892-0-P

Page 1 of 1

**Project:** 60493017

**Description :** Stack Emission Samples

**Date :** 05-Dec-17

Received: 30-Nov-17

**Report To :** James Lang

**Copy to:** FILE

17 Warabrook Blvd, Warabrook NSW 2304

Thimble ID		Volume (mL)	Total Particulate Matter (g)
T368	Filter	-	0.0003
T523	Filter	-	0.0007



NATA Accredited Laboratory 18079

Accredited for compliance with  
ISO/IEC 17025 - Testing

Note : *Sampled by Client*

**Reported By:** M. Campbell

Michael Campbell

Determined in Accordance With:  
Particulate matter - total in stack gases by  
gravimetric using in-house M300;  
Acetone/Water Rinse using AS4323.2

# Steel River Testing

5/11 McIntosh Drive, Mayfield West, NSW 2304  
Phone: 02 49677880

## STACK EMISSION - MOISTURE REPORT

**Origin:** AECOM - Newcastle  
**Project:** 60493017  
**Report :** 14892-0-M Page 1 of 1  
**Description :** Stack Emission Samples  
Received: 30-Nov-17  
**Date :** 05-Dec-17  
**Report To :** James Lang  
17 Warabrook Blvd, Warabrook NSW 2304  
**Copy to:** FILE

---

Jar ID	Moisture (g)
135	16.2
DT10	15.5
F26	10.7



NATA Accredited Laboratory 18079  
Accredited for compliance with  
ISO/IEC 17025 - Testing

**Reported By:** M. Campbell  
Michael Campbell

Determined in Accordance With:  
Moisture content in stack gases by gravimetric  
using in-house M301

### CLIENT DETAILS

Contact **Cye Buckland**  
Client **AECOM Australia Pty Ltd**  
Address **17 Warabrook Boulevard  
Warabrook  
SYDNEY NSW 2304**

Telephone **02 8295 3600**  
Facsimile **02 8934 0001**  
Email **cye.buckland@aecom.com**

Project **60493017-2.1**  
Order Number **60493017-2.1**  
Samples **12**

### LABORATORY DETAILS

Manager **Adam Atkinson**  
Laboratory **SGS Melbourne EH&S**  
Address **10/585 Blackburn Road  
Notting Hill Victoria 3168**

Telephone **+61395743200**  
Facsimile **+61395743399**  
Email **Au.SampleReceipt.Melbourne@sgs.com**

SGS Reference **ME304956 R0**  
Date Received **24 Nov 2017**  
Date Reported **05 Dec 2017**

### COMMENTS

Accredited for compliance with ISO/IEC 17025 - Testing. NATA accredited laboratory 2562(14420).

### SIGNATORIES

MING

Weiming Dai  
Inorganic Supervisor

MING

Weiming Dai  
Senior Chemist

Parameter	Units	LOR	Sample Number Sample Matrix Sample Name	ME304956.001 Filter Flakt 1 Metals 1	ME304956.002 Filter Metals 12	ME304956.003 Impinger Solution Flakt 1 Metals 3	ME304956.004 Impinger Solution Flakt 1 Metals 4
-----------	-------	-----	---	--	-------------------------------------	--	--

**Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29\_FILT Tested: 4/12/2017**

Sb	µg total	0.2	<0.2	<0.2	-	-
As	µg total	0.2	<0.2	0.2	-	-
Be	µg total	0.2	<0.2	<0.2	-	-
Cd	µg total	0.2	1.6	<0.2	-	-
Cr	µg total	0.2	0.8	1.0	-	-
Co	µg total	0.2	<0.2	<0.2	-	-
Cu	µg total	0.2	1.1	1.0	-	-
Pb	µg total	0.2	0.4	0.2	-	-
Mg	µg total	2	41	58	-	-
Mn	µg total	0.2	0.8	1.0	-	-
Hg	µg total	0.2	<0.2	<0.2	-	-
Ni	µg total	0.2	<0.2	0.2	-	-
Se	µg total	0.2	0.3	<0.2	-	-
Tl	µg total	0.2	<0.2	<0.2	-	-
Sn	µg total	0.2	0.3	0.4	-	-
V	µg total	0.2	2.0	2.9	-	-
Zn	µg total	0.2	1000	1400	-	-

**Metals in Impingers M29 ETC MA-1400.IMP.M29.06 (ug total) Method: EPA29\_METIMP Tested: 4/12/2017**

Sb	µg total	0.1	-	-	<0.1	<0.1
As	µg total	0.1	-	-	<0.1	<0.1
Be	µg total	0.1	-	-	<0.1	<0.1
Cd	µg total	0.1	-	-	<0.1	0.4
Cr	µg total	0.1	-	-	<0.1	0.3
Co	µg total	0.1	-	-	<0.1	<0.1
Cu	µg total	0.1	-	-	<0.1	0.5
Pb	µg total	0.1	-	-	<0.1	<0.1
Mg	µg total	0.1	-	-	<0.1	<0.1
Mn	µg total	0.1	-	-	<0.1	3.5
Hg	µg total	0.1	-	-	<0.1	<0.1
Ni	µg total	0.1	-	-	<0.1	0.1
Se	µg total	0.1	-	-	0.6	0.7
Tl	µg total	0.1	-	-	<0.1	<0.1
Sn	µg total	0.1	-	-	<0.1	9.9
V	µg total	0.1	-	-	0.7	2.6
Zn	µg total	0.1	-	-	<0.1	<0.1
Sample Volume*	mL	-	-	-	94	320

Parameter	Units	LOR	Sample Number Sample Matrix Sample Name	ME304956.005 Impinger Solution Metals 8A	ME304956.006 Impinger Solution Metals 9	ME304956.007 Impinger Solution Flakt 1 Metals 5A	ME304956.008 Impinger Solution Flakt 1 Metals 5C
-----------	-------	-----	---	---	--	---	---

**Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29\_FILT Tested: 4/12/2017**

Sb	µg total	0.2	-	-	-	-
As	µg total	0.2	-	-	-	-
Be	µg total	0.2	-	-	-	-
Cd	µg total	0.2	-	-	-	-
Cr	µg total	0.2	-	-	-	-
Co	µg total	0.2	-	-	-	-
Cu	µg total	0.2	-	-	-	-
Pb	µg total	0.2	-	-	-	-
Mg	µg total	2	-	-	-	-
Mn	µg total	0.2	-	-	-	-
Hg	µg total	0.2	-	-	-	-
Ni	µg total	0.2	-	-	-	-
Se	µg total	0.2	-	-	-	-
Tl	µg total	0.2	-	-	-	-
Sn	µg total	0.2	-	-	-	-
V	µg total	0.2	-	-	-	-
Zn	µg total	0.2	-	-	-	-

**Metals in Impingers M29 ETC MA-1400.IMP.M29.06 (ug total) Method: EPA29\_METIMP Tested: 1/12/2017**

Sb	µg total	0.1	<0.1	<0.1	-	-
As	µg total	0.1	<0.1	<0.1	-	-
Be	µg total	0.1	<0.1	<0.1	-	-
Cd	µg total	0.1	<0.1	<0.1	-	-
Cr	µg total	0.1	<0.1	<0.1	-	-
Co	µg total	0.1	<0.1	<0.1	-	-
Cu	µg total	0.1	0.2	<0.1	-	-
Pb	µg total	0.1	<0.1	<0.1	-	-
Mg	µg total	0.1	<0.1	<0.1	-	-
Mn	µg total	0.1	0.8	8.6	-	-
Hg	µg total	0.1	<0.1	<0.1	<0.1	<0.1
Ni	µg total	0.1	<0.1	<0.1	-	-
Se	µg total	0.1	0.4	0.9	-	-
Tl	µg total	0.1	<0.1	<0.1	-	-
Sn	µg total	0.1	<0.1	9.2	-	-
V	µg total	0.1	2.4	1.8	-	-
Zn	µg total	0.1	1.0	<0.1	-	-
Sample Volume*	mL	-	310	200	100	250

Sample Number	ME304956.009	ME304956.010	ME304956.011	ME304956.012
Sample Matrix	Impinger	Impinger	KMnO4	KMnO4
Sample Name	Solution Metals 8B	Solution Metals 11	Flakt 1 Metals 5B	Metals 10

Parameter	Units	LOR				
<b>Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29_FILT Tested: 4/12/2017</b>						
Sb	µg total	0.2	-	-	-	-
As	µg total	0.2	-	-	-	-
Be	µg total	0.2	-	-	-	-
Cd	µg total	0.2	-	-	-	-
Cr	µg total	0.2	-	-	-	-
Co	µg total	0.2	-	-	-	-
Cu	µg total	0.2	-	-	-	-
Pb	µg total	0.2	-	-	-	-
Mg	µg total	2	-	-	-	-
Mn	µg total	0.2	-	-	-	-
Hg	µg total	0.2	-	-	-	-
Ni	µg total	0.2	-	-	-	-
Se	µg total	0.2	-	-	-	-
Tl	µg total	0.2	-	-	-	-
Sn	µg total	0.2	-	-	-	-
V	µg total	0.2	-	-	-	-
Zn	µg total	0.2	-	-	-	-

<b>Metals in Impingers M29 ETC MA-1400.IMP.M29.06 (ug total) Method: EPA29_METIMP Tested: 1/12/2017</b>						
Sb	µg total	0.1	-	-	-	-
As	µg total	0.1	-	-	-	-
Be	µg total	0.1	-	-	-	-
Cd	µg total	0.1	-	-	-	-
Cr	µg total	0.1	-	-	-	-
Co	µg total	0.1	-	-	-	-
Cu	µg total	0.1	-	-	-	-
Pb	µg total	0.1	-	-	-	-
Mg	µg total	0.1	-	-	-	-
Mn	µg total	0.1	-	-	-	-
Hg	µg total	0.1	<0.1	<0.1	<0.1	<0.1
Ni	µg total	0.1	-	-	-	-
Se	µg total	0.1	-	-	-	-
Tl	µg total	0.1	-	-	-	-
Sn	µg total	0.1	-	-	-	-
V	µg total	0.1	-	-	-	-
Zn	µg total	0.1	-	-	-	-
Sample Volume*	mL	-	98	250	400	100



MB blank results are compared to the Limit of Reporting

LCS and MS spike recoveries are measured as the percentage of analyte recovered from the sample compared the the amount of analyte spiked into the sample.

DUP and MSD relative percent differences are measured against their original counterpart samples according to the formula : *the absolute difference of the two results divided by the average of the two results as a percentage*. Where the DUP RPD is 'NA' , the results are less than the LOR and thus the RPD is not applicable.

Metals in Filters M29 ETC MA-1400.FL.M29.02 USEPA M29 Method: EPA29\_FILTER

Parameter	QC Reference	Units	LOR	MB	LCS %Recovery
Sb	LB017281	µg total	0.2	<0.2	NA
As	LB017281	µg total	0.2	<0.2	NA
Be	LB017281	µg total	0.2	<0.2	NA
Cd	LB017281	µg total	0.2	<0.2	NA
Cr	LB017281	µg total	0.2	<0.2	NA
Co	LB017281	µg total	0.2	<0.2	NA
Cu	LB017281	µg total	0.2	<0.2	NA
Pb	LB017281	µg total	0.2	<0.2	NA
Mg	LB017281	µg total	2	<2	NA
Mn	LB017281	µg total	0.2	<0.2	NA
Hg	LB017281	µg total	0.2	<0.2	NA
Ni	LB017281	µg total	0.2	<0.2	NA
Se	LB017281	µg total	0.2	<0.2	NA
Tl	LB017281	µg total	0.2	<0.2	NA
Sn	LB017281	µg total	0.2	<0.2	NA
V	LB017281	µg total	0.2	<0.2	NA
Zn	LB017281	µg total	0.2	<0.2	NA

Metals in Impingers M29 ETC MA-1400.IMP.M29.06 (ug total) Method: EPA29\_METIMP

Parameter	QC Reference	Units	LOR	MB	LCS %Recovery
Sb	LB017303	µg total	0.1	<0.1	102%
As	LB017303	µg total	0.1	<0.1	102%
Be	LB017303	µg total	0.1	<0.1	93%
Cd	LB017303	µg total	0.1	<0.1	101%
Cr	LB017303	µg total	0.1	<0.1	98%
Co	LB017303	µg total	0.1	<0.1	96%
Cu	LB017303	µg total	0.1	<0.1	100%
Pb	LB017303	µg total	0.1	<0.1	107%
Mg	LB017303	µg total	0.1	<0.1	95%
Mn	LB017303	µg total	0.1	<0.1	100%
Hg	LB017303	µg total	0.1	<0.1	100%
Ni	LB017303	µg total	0.1	<0.1	98%
Se	LB017303	µg total	0.1	<0.1	104%
Tl	LB017303	µg total	0.1	<0.1	107%
Sn	LB017303	µg total	0.1	<0.1	102%
V	LB017303	µg total	0.1	<0.1	98%
Zn	LB017303	µg total	0.1	<0.1	102%
Sample Volume*	LB017303	mL	-	1.0	NA

METHOD

METHODOLOGY SUMMARY

EPA 29

Analysis of acid-leachable metals by Inductively Coupled Plasma-Mass Spectrometer (ICP-MS). This method is based on USEPA 3051A, USEPA M29, and USEPA 6020A.  
 . Filters are digested using the appropriate sample preparation methods.  
 A representative sample is extracted in concentrated acid using microwave heating by the CEM -MarsXPress (with Built-in USEPA method) Microwave Digestion system. The sample and acid are placed in a microwave vessel (TFM), which is then capped and heated in the microwave unit. After cooling, the vessel contents are diluted with DI water, then filtered/settled/centrifuged and analysed by ICP MS.

EPA29

This method covers the analysis of acid-leachable metals by Inductively Coupled Plasma-Mass Spectrometer (ICP-MS). This method is based on USEPA M29, USEPA 3015A and USEPA 6020A.  
 Prior to analysis, samples are be solubilised or digested using the appropriate sample preparation methods.

FOOTNOTES

IS	Insufficient sample for analysis.	LOR	Limit of Reporting
LNR	Sample listed, but not received.	↑↓	Raised or Lowered Limit of Reporting
*	NATA accreditation does not cover the performance of this service.	QFH	QC result is above the upper tolerance
**	Indicative data, theoretical holding time exceeded.	QFL	QC result is below the lower tolerance
		-	The sample was not analysed for this analyte
		NVL	Not Validated

Samples analysed as received.  
 Solid samples expressed on a dry weight basis.

Where "Total" analyte groups are reported (for example, Total PAHs, Total OC Pesticides) the total will be calculated as the sum of the individual analytes, with those analytes that are reported as <LOR being assumed to be zero. The summed (Total) limit of reporting is calculated by summing the individual analyte LORs and dividing by two. For example, where 16 individual analytes are being summed and each has an LOR of 0.1 mg/kg, the "Totals" LOR will be 1.6 / 2 (0.8 mg/kg). Where only 2 analytes are being summed, the " Total" LOR will be the sum of those two LORs.

Some totals may not appear to add up because the total is rounded after adding up the raw values.

If reported, measurement uncertainty follow the ± sign after the analytical result and is expressed as the expanded uncertainty calculated using a coverage factor of 2, providing a level of confidence of approximately 95%, unless stated otherwise in the comments section of this report.

Results reported for samples tested under test methods with codes starting with ARS-SOP, radionuclide or gross radioactivity concentrations are expressed in becquerel (Bq) per unit of mass or volume or per wipe as stated on the report. Becquerel is the SI unit for activity and equals one nuclear transformation per second.

Note that in terms of units of radioactivity:

- a. 1 Bq is equivalent to 27 pCi
- b. 37 MBq is equivalent to 1 mCi

For results reported for samples tested under test methods with codes starting with ARS-SOP, less than (<) values indicate the detection limit for each radionuclide or parameter for the measurement system used. The respective detection limits have been calculated in accordance with ISO 11929.

The QC criteria are subject to internal review according to the SGS QAQC plan and may be provided on request or alternatively can be found here : [http://www.sgs.com.au/-/media/Local/Australia/Documents/ Technical%20Documents/MP-AU-ENV-QU-022%20QA%20QC%20Plan.pdf](http://www.sgs.com.au/-/media/Local/Australia/Documents/Technical%20Documents/MP-AU-ENV-QU-022%20QA%20QC%20Plan.pdf)

This document is issued by the Company under its General Conditions of Service accessible at [www.sgs.com/en/Terms-and-Conditions.aspx](http://www.sgs.com/en/Terms-and-Conditions.aspx). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client only. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law .

This report must not be reproduced, except in full.

